

LD型电动单梁起重机

LD Model Motor-driven Single Beam Crane

LD型电动单梁起重机

LD Model Motor-driven Single Beam Crane

吨位 (t)	跨度 (m) S	整车总重 (G)t 地面操作	最大轮压 Rmax (kN)	最小轮压 Rmin (kN)	踏面至主梁顶 H1	踏面至钩中心 H2	主梁总高 H3	端梁轮距 W	端梁总长 B	吊钩左极限 C1	吊钩右极限 C2						
1	19	3.01	12.7	7.2	530	970	650	2500									
	19.5	3.02	12.7	7.2													
	20	3.20	13.1	7.7													
	20.5	3.26	13.3	7.8	580	970	700	3000	3500								
	21	3.32	13.4	8.0													
	21.5	3.37	13.6	8.1													
	22	3.43	13.7	8.2													
	22.5	3.49	13.9	8.4													
	23	4.07	15.3	9.8	660	990	800	3500	4000								
	23.5	4.13	15.5	10.0													
	24	4.20	15.7	10.2													
	24.5	4.26	15.8	10.3													
	25	4.32	16.0	10.5													
	25.5	4.39	16.2	10.6													
	26	5.35	18.6	13.0								745	1010	900	4000	4500	
26.5	5.43	18.8	13.2														
27	5.52	19.0	13.5														
27.5	5.60	19.2	13.7														
28	5.68	19.4	13.9														
28.5	5.76	19.6	14.1														
7.5	1.79	13.8	4.1	490	1080	550	2000	2500	871	1274							
8	1.84	14.0	4.2														
8.5	1.88	14.1	4.3														
9	1.93	14.3	4.4														
9.5	1.98	14.5	4.5														
10	2.03	14.7	4.6														
10.5	2.07	14.8	4.7														
11	2.12	15.0	4.8		1125	595											
11.5	2.25	15.4	5.1														
12	2.30	15.5	5.3														
12.5	2.35	15.7	5.4														
13	2.40	15.8	5.5														
13.5	2.45	16.0	5.6														
14	2.50	16.1	5.8									580	1140	700			
14.5	2.62	16.5	6.1														
15	2.68	16.6	6.2														
15.5	2.74	16.8	6.3														
16	2.79	17.0	6.5														
16.5	2.85	17.1	6.6														
17	2.91	17.3	6.8	2500	3000												
17.5	3.23	18.1	7.6														
18	3.30	18.3	7.7														
18.5	3.36	18.5	7.9														
19	3.42	18.6	8.0														
19.5	3.49	18.8	8.2								660	1160	800				
20	3.56	19.0	8.3														
20.5	3.63	19.2	8.4														
21	3.70	19.4	8.5														
21.5	3.77	19.6	8.6														
22	3.84	19.8	8.7														
22.5	3.91	20.0	8.8														

吨位 (t)	跨度 (m) S	整车总重 (G)t 地面操作	最大轮压 Rmax (kN)	最小轮压 Rmin (kN)	踏面至主梁顶 H1	踏面至钩中心 H2	主梁总高 H3	端梁轮距 W	端梁总长 B	吊钩左极限 C1	吊钩右极限 C2
2	20	4.09	20.3	9.7	785	1135	900	3000	3500	871	1274
	20.5	4.17	20.5	9.9							
	21	4.24	20.7	10.1							
	21.5	4.32	20.9	10.3							
	22	4.40	21.1	10.5							
	22.5	4.47	21.3	10.7	820	1200	1000	3500	4000		
	23	5.31	23.4	12.7							
	23.5	5.40	23.7	13.0							
	24	5.49	23.9	13.2							
	24.5	5.57	24.1	13.4							
	25	5.66	24.3	13.6	875	1250	1100	4000	4500		
	25.5	5.75	24.6	13.8							
	26	6.40	26.2	15.5							
	26.5	6.50	26.5	15.7							
	27	6.60	26.7	16.0							
27.5	6.69	27.0	16.2								
28	6.79	27.2	16.4								
28.5	6.89	27.5	16.7	530	1255	650	2000	2500	818.5	1291	
7.5	1.93	18.9	4.2								
8	1.98	19.1	4.3								
8.5	2.03	19.4	4.4								
9	2.09	19.6	4.5								
9.5	2.14	19.8	4.7								
10	2.20	20.0	4.8								
10.5	2.25	20.2	4.9								
11	2.31	20.4	5.0		580		700				
11.5	2.41	20.7	5.3								
12	2.47	20.9	5.4								
12.5	2.53	21.1	5.6								
13	2.59	21.3	5.7								
13.5	2.64	21.5	5.9								
14	2.70	21.7	6.0								
14.5	3.02	22.5	6.8	660	1275	800	2500	3000			
15	3.08	22.7	6.9								
15.5	3.14	22.9	7.1								
16	3.21	23.1	7.2								
16.5	3.27	23.2	7.4								
17	3.34	23.4	7.6								
17.5	3.84	24.7	8.8								745
18	3.91	24.9	9.0								
18.5	3.99	25.1	9.2								
19	4.06	25.3	9.4								
19.5	4.14	25.5	9.6								
20	4.92	27.5	11.5								
20.5	5.01	27.7	11.7	820	1315	1100	3000	3500			
21	5.09	28.0	11.9								
21.5	5.18	28.2	12.2								
22	5.27	28.4	12.4								



卫华集团 WEIHUA CRANE



中国驰名商标

中国机械百强