

LD型电动单梁起重机

LD Model Motor-driven Single Beam Crane

LD型电动单梁起重机

LD Model Motor-driven Single Beam Crane

吨位 (t)	跨度 (m) S	整车总重 (G)t 地面操作	最大轮压 Rmax (kN)	最小轮压 Rmin (kN)	踏面至主梁顶 H1	踏面至钩中心 H2	主梁总高 H3	端梁轮距 W	端梁总长 B	吊钩左极限 C1	吊钩右极限 C2
10	25	9.56	73.8	21.4	1100	1920	1350	3500	4000	1293	1893
	25.5	9.71	74.2	21.7							
	26	13.09	82.7	30.2	1200		1450	4000	4700		
	26.5	13.29	83.3	30.7							
	27	13.48	83.8	31.2							
	27.5	13.67	84.3	31.6							
	28	13.86	84.8	32.1							
	28.5	14.05	85.4	32.6							
16	7.5	3.64	77.2	7.0	820	2480	1000	2000	2500	1293	1893
	8	3.74	78.3	7.2							
	8.5	3.84	79.4	7.4							
	9	3.94	80.4	7.6							
	9.5	4.04	81.3	7.9							
	10	4.14	82.1	8.1							
	10.5	4.24	82.9	8.3							
	11	4.34	83.6	8.5							
	11.5	4.55	84.6	9.0							
	12	4.66	85.2	9.3							
	12.5	4.76	85.9	9.5							
	13	4.87	86.5	9.8							
	13.5	4.97	87.1	10.0							
	14	5.08	87.6	10.3							
	14.5	5.93	90.0	12.4							
	15	6.06	90.6	12.7							
	15.5	6.18	91.1	13.0							
	16	6.31	91.7	13.3							
	16.5	6.43	92.2	13.6							
	17	6.56	92.7	13.9							
	17.5	7.19	94.5	15.5							
	18	7.33	95.0	15.8							
	18.5	7.47	95.5	16.1							
	19	7.61	96.0	16.5							
	19.5	7.75	96.5	16.8							
	20	8.56	98.7	18.9							
	20.5	8.72	99.2	19.2							
	21	8.87	99.7	19.6							
	21.5	9.03	100.2	20.0							
	22	9.18	100.8	20.4							
	22.5	9.34	101.3	20.8							
	23	12.41	109.0	28.4							
23.5	12.61	109.6	28.9								
24	12.81	110.2	29.4								
24.5	13.02	110.9	30.0								
25	13.22	111.5	30.5								
25.5	13.43	112.0	31.0								

吨位 (t)	跨度 (m) S	整车总重 (G)t 地面操作	最大轮压 Rmax (kN)	最小轮压 Rmin (kN)	踏面至主梁顶 H1	踏面至钩中心 H2	主梁总高 H3	端梁轮距 W	端梁总长 B	吊钩左极限 C1	吊钩右极限 C2
16	26	14.34	114.4	33.2	1300	2600	1600	4000	4700		
	26.5	14.55	115.0	33.8							
	27	14.77	115.6	34.3							
	27.5	14.98	116.3	34.8							
	28	15.20	116.9	35.4							
	28.5	15.42	117.5	35.9							
20	7.5	5.45	97.9	10.2	900	2450	1050	2000	2700	1394	1933
	8	5.58	99.5	10.5							
	8.5	5.70	101.0	10.7							
	9	5.83	102.3	11.0							
	9.5	5.96	103.5	11.3							
	10	6.09	104.6	11.6							
	10.5	6.22	105.7	11.8							
	11	6.35	106.6	12.1							
	11.5	6.99	108.8	13.7							
	12	7.15	109.8	14.0							
	12.5	7.30	110.7	14.4							
	13	7.45	111.5	14.7							
	13.5	7.60	112.3	15.1							
	14	7.76	113.1	15.5							
	14.5	8.67	115.8	17.7							
	15	8.85	116.6	18.1							
	15.5	9.02	117.3	18.6							
	16	9.20	118.1	19.0							
	16.5	9.37	118.8	19.4							
	17	9.55	119.5	19.8							
	17.5	10.50	122.2	22.2							
	18	10.70	122.9	22.7							
	18.5	10.89	123.6	23.1							
	19	11.09	124.3	23.6							
	19.5	11.28	125.0	24.1							
	20	12.02	127.0	25.9							
	20.5	12.23	127.7	26.4							
	21	12.44	128.4	26.9							
	21.5	12.64	129.1	27.4							
	22	12.85	129.8	27.9							
	22.5	12.96	130.5	28.5							
	23	13.88	132.7	30.5							
23.5	14.10	133.4	31.0								
24	14.31	134.0	31.6								
24.5	14.52	134.78	32.1								
25	14.74	135.4	32.6								
25.5	14.96	135.6	33.1								

*注：司机室操作时起重机总重增加0.5t，最大、最小轮压均增加2kN。
如有其他要求，请在订货时特别提出。
我公司保留在无需任何通知的情况下对以上信息进行变更的权力。



卫华集团
WEIHUA
CRANE



中国驰名商标

中国机械百强